


**Flanged End, 2 Piece, Full Port,
Class 150, Size 65-150**

SERIES 74 - F2



SIZE	DIMENSIONAL DATA IN MM									NO. OF HOLES	QTY	TAG NO.
	A	NW	H	X	ØD	b	Øg	PCD	Hole Ø			
65	190	63.5	152	505	178	17.5	105	139.7	19	4		
80	203	76	151	505	191	19	129	152.4	19	4		
100	229	102	280	600	229	24	157	190.5	19	8		
150	267	152	225	600	279	25.5	216	241.3	22	8		



Manufacturing Standard : BS 5351
Hydrostatic & Pneumatic : BS 5146

Test For Class 150

Shell Hydro 31 kg/cm²
Seat Hydro 19.5 kg/cm²
Seat Air 7 Kg/cm²

Flanged to ANSI -B 16.5 RF - Standard
Fire safe with antistatic device and other
flange drilling on request

NO.	PART NAME	MATERIAL							
1	Body	A	B	C	D	H	a	J	
2	Side Piece	A	B	C	D	H	a	J	
3	Gland	G	E	F	D	U	b	J	
4	Ball	B	C	C	D	H	a	J	
5	Stem	E	F	G	D	U	b	J	
6	Ball Seat	PTFE			GFT		GRAFOIL		
7	Stem Seal	PTFE			GFT		GRAFOIL		
8	Gland Packings	PTFE			GFT		GRAFOIL		
9	Body Seal	PTFE			GFT		GRAFOIL		
10	Adapter	STEEL							
11	Bolt	L				R			
12	Check Nut	STEEL							
13	Stopper	STEEL							
14	Body Stud / Nut	E	L	M	N	R	S	T	
15	Pipe Wrench	C CLASS (PIPE)							

A = ASTM A-216 Gr.WCB
B = ASTM A-351 Gr.CF8
C = ASTM A-351 Gr.CF8M
D = ASTM A-351 Gr.CN7M
E = AISI - 304
F = AISI - 316
G = AISI - 410
H = ASTM A-351 Gr.CF3
J = ASTM A-494 CW 12 M1
L = ASTM A-193 Gr.B7 / Gr.10.9
M = ASTM A-93 Gr. B8
N = ASTM A-193 Gr. B8M
P = ASTM A-217 Gr. CA15
a = ASTM A-351 Gr.CF3M
b = AISI - 316L
R = ASTM A-194 Gr.2H
S = ASTM A-194 Gr.8
T = ASTM A-194 Gr.8M
U = AISI - 304L
PTFE = POLY TETRA FLUORO ETHYLENE
GFT = GLASS FILLED TEFLON

CUSTOMER :
 ORDER NO :
 JOB/PROJECT :

Development is continuous and specifications are subject to alterations at any time without notice

Drg. No : ACVPL/74-F2/50-250 / 2 PC

OUR Ref :

Aqua Control Valves Pvt. Ltd.,
 D/72, C/67, Industrial Estate,
 Udyambag, BELGAUM - 590 008
 Karnataka State,
 INDIA